

MULTICUT 570 / 575

RUGGED FLOOR SAWS FOR THE TOUGHEST JOB SITE CHALLENGES

- **MULTICUT 570: Rear pivot**
- **MULTICUT 575: Front pivot**

- High powered HATZ Diesel provides abundant torque and blade speed
- MULTICUT 570 is in full compliance with the emission regulations of US Tier 4 final
- Hydrostatic drive provides even and controlled propulsion
- 4-Speed gearbox
- Tortion resistant frame
- Electro hydraulic saw blade adjustment
- 3 position height adjustable handles for ergonomic operation
- Convenient transition between left and right hand cutting
- Easy access for service and preventive maintenance



MULTICUT 570
Stage V Version pictured

TECHNICAL DATA	MULTICUT 570	MULTICUT 575
Cutting depth max.	17 inch (432 mm)	17 inch (432 mm)
Cutting depth setting	electro hydraulic/smoothly adjustable	electro hydraulic/smoothly adjustable
Saw blade dia. max.	40 inch (1000 mm)	40 inch (1000 mm)
Saw blade holder	1.00 inch (25.4 mm)	1.00 inch (25.4 mm)
Forward speed	hydrostatic stepless 165 ft/min (0-50 m/min)	hydrostatic stepless 165 ft/min (0-50 m/min)
Reverse speed	hydrostatic stepless 83 ft/min (0-25 m/min)	hydrostatic stepless 83 ft/min (0-25 m/min)
Engine	HATZ diesel 3-cylinder	HATZ diesel 3-cylinder
Output power max.	56 hp	56 hp
Emission level	EPA Tier IV Final	EPA Tier IV Final
Saw blade speed (optional)	800 / 1300 / 1900 / 2800 rpm	800 / 1300 / 1900 / 2800 rpm
Dimensions without blade guard (L/W/H)	51.6/31.5/48.5 inch (1310/800/1232 mm)	59/30.5/48.5 inch (1500/775/1232 mm)
Weight	1650 lbs (748 kg)	1750 lbs (794 kg)
Left/right hand cut	yes	yes