

FS20 FLUSH CUT SAW AND BLADES

MOVE UP IN THE WORLD OR DOWN DEEP INTO A PROJECT WITH RGC'S FLUSH CUT SAW

FS20 Flush Cut Saw

All saws include Guard, Water Attachment for wet cutting, Hose whips w/ Flush-Face fittings and Trigger Lockout. (Hydraulic requirements: 8 gpm @ 2000-2500 psi.)

Part #	Description	Weight
2020305	FS20 Hand Saw, Guard and Depth Guide w/ 8 in. cutting depth. 1830 rpm @ 8 gpm	57 lbs.
2020201	FS20 Hand Saw, Guard, Depth Guide and Upright Handle w/ 8 in. cutting depth. 1830 rpm @ 8 gpm	98 lbs.
2020203	FS20 Upright Saw w/ 8 in. cutting depth. 1830 rpm @ 8 gpm	83 lbs.
2020409	FS20 Upright Handle Kit	41 lbs.

FS20 Flush Cut Blades

Part #	Description
Premium Blades	
5252001	20 in. x .125 in. – with Heavy Rebar
5252002	20 in. x .125 in. – with Standard Rebar
Standard Blades	
5212211	21 in. x .125 in. – Abrasive without Rebar
5212212	21 in. x .125 in. – Med-soft, very-Hard with Rebar
5212213	21 in. x .145 in. – Abrasive without Rebar
5212214	21 in. x .145 in. – Med-soft, very-Hard with Rebar

