

2021











BUILT TO LAST





Since we started business back in 1946, RGC has maintained a standard for excellence in technology and durability. For over 75 years, RGC has provided safe and simple solutions so you can get the job done. Through our focus on intelligent engineering, low maintenance and superior functionality, RGC products put you ahead of the game.

This year marks RGC's 75th anniversary, and we are excited to celebrate this monumental milestone. We extend our sincere thanks to our dealers and customers for 75 years of loyalty and support. We will thank you by continuing to do what we do best: Provide you with the most innovative and durable products so you can get the job done!

Table of Contents

	Page #
HydraCutter C150™ and Accessories	3
HydraCutter C120™ and Accessories	4
HydraCutter C50	5
FS20 Flush Cut Saw & Blades	6
Hydrasaws & Hydracarts	7
Hydrapaks with Gas Engines	8
Hydrapaks with Electric Motors	9
Hydraulic Water, Trash Pumps & Core Drills	10
Platform Hoists	11
* * * Prices and products subject to change without notice. Freight F.O.B., Buffalo, N	/ * * *

OUR QUALITY PLEDGE TO YOU

At RGC, quality is more than a word — it's a standard by which we promise to work. For 75 years, we have consistently manufactured the best products for the most demanding environments. From concept to creation, our products are innovative, efficient and built to last. We continually invest in our processes, our technology and our people to deliver the highest caliber product to every customer worldwide.



HydraCutter C150[™] and Accessories



HydraCutter C150™

THE HEAVY DUTY SAW FOR THE BIGGEST JOBS

- 8 gpm at 2000 to 2500 psi cutting power
- 12 gpm at 2000 to 2500 psi cutting power
- An S-series chain for cutting medium-soft to very hard aggregate with moderate to heavy steel reinforcing

An L-series chain for cutting newer concrete, brick and concrete block without steel reinforcing

Your choice of a 15", 20" or 30" tapered bar with a roller nose sprocket and internal water ports for maximum bar and chain life.

HydraCutter C150™			
Part #	Model	Description	
1914010	C150-8	C150-8 GPM w/ 15 in. Bar & 76-S or 76-L Chain	
1914012	C150-8	C150-8 GPM w/ 20 in. Bar & 88-S or 88-L Chain	
1914002	C150-12	C150-12 GPM w/ 15 in. Bar & 62-S or 62-L Chain	
1914004	C150-12	C150-12 GPM w/ 20 in. Bar & 72-S or 72-L Chain	
1914006	C150-12	C150-12 GPM w/ 30 in. Bar & 90-S or 90-L Chain	

		utter C150™ – 8 GPM s, Chains & Parts
Part #	Model	Description
1927015		15 in. Bar (38 cm)
1927020		20 in. Bar (51 cm)
5260761	76-S	Chain for 15 in. Bar (Replaces SL25-76)
5260762	76-L	Chain for 15 in. Bar (Replaces SL45-76)
5260881	88-S	Chain for 20 in. Bar (Replaces SL25-88)
5260882	88-L	Chain for 20 in. Bar (Replaces SL45-88)
1907135		8 GPM Drive Sprocket (18 Tooth)
5807195		Trantorque® Shaft Adapter
1909609		ILP™ Auxiliary Hydraulic In-Line Pump

C150™ Cast Speedhook – 42in.

1914101

HydraCutter C150™ – 12 GPM Bars, Chains & Parts			
Part #	Model	Description	
1945615		15 in. Bar (38 cm)	
1945620		20 in. Bar (51 cm)	
1945630		30 in. Bar (76 cm)	
5245601	62-S	Chain for 15 in. Bar	
5245603	62-L	Chain for 15 in. Bar	
5245611	72-S	Chain for 20 in. Bar	
5245613	72-L	Chain for 20 in. Bar	
5245621	90-S	Chain for 30 in. Bar	
5245623	90-L	Chain for 30 in. Bar	
1914801		12 GPM Drive Sprocket (15 Tooth)	
5807195		Trantorque® Shaft Adapter	
1914101		C150™ Cast Speedhook – 42in.	

15 Tooth)	
pter	
- 42in.	
	•

HydraCutter C120™ & Accessories

C120™ HYDRACUTTER

MEET THE HYDRAULIC SAW THAT WILL STAY HOT EVEN WHEN THE TEMPERATURES GET FRIGID

Available with your choice of diamond-segmented chains:

- An S-series chain for cutting medium-soft to very hard aggregate with moderate to heavy steel reinforcing
- An L-series chain for cutting newer concrete, brick and concrete block without steel reinforcing

HydraC	utter C1	20™ - 12 GPM w/ Bar & Chains
Part #	Model	Description
1919120	C120-12	C120-12 gpm Power Head only
1919121	C120-12	C120-12 gpm w/ 10 in. Bar & 50-L Chain
1919122	C120-12	C120-12 gpm w/ 10 in. Bar & 50-S Chain
1919123	C120-12	C120-12 gpm w/ 15 in. Bar & 57-L Chain
1919124	C120-12	C120-12 gpm w/ 15 in. Bar & 57-S Chain
1919125	C120-12	C120-12 gpm w/ 20 in. Bar & 67-L Chain
1919126	C120-12	C120-12 gpm w/ 20 in. Bar & 67-S Chain
1919127	C120-12	C120-12 gpm w/ 25 in. Bar & 79-L Chain
1919128	C120-12	C120-12 gpm w/ 25 in. Bar & 79-S Chain
1919129	C120-12	C120-12 gpm w/ 30 in. Bar & 90-L Chain
1919130	C120-12	C120-12 gpm w/ 30 in. Bar & 90-S Chain



	Hydra	Cutter C120™ Chains
Part #	Model	Description
5245701	50-L	C120 Chain for 10 in. bar, .456 Pitch
5245703	50-S	C120 Chain for 10 in. bar, .456 Pitch
5245711	57-L	C120 Chain for 15 in. bar, .456 Pitch
5245713	57-S	C120 Chain for 15 in. bar, .456 Pitch
5245721	67-L	C120 Chain for 20 in. bar, .456 Pitch
5245723	67-S	C120 Chain for 20 in. bar, .456 Pitch
5245731	79-L	C120 Chain for 25 in. bar, .456 Pitch
5245733	79-S	C120 Chain for 25 in. bar, .456 Pitch
5245623	90-L	C120 Chain for 30 in. bar, .456 Pitch
5245621	90-S	C120 Chain for 30 in. bar, .456 Pitch

HydraCutter C120™ Bars and Parts			
Part #	Description		
1945710	10 in. Bar (25.4 cm)		
1945715	15 in. Bar (38.1 cm)		
1945720	20 in. Bar (50.8 cm)		
1945725	25 in. Bar (63.5 cm)		
1945730	30 in. Bar (76.2 cm)		
6719912	12 gpm Drive Sprocket (12 Tooth)		

HydraCutter C50 & Accessories



C50 HYDRACUTTER THE PINT-SIZED POWERHOUSE FOR ALL YOUR CHAINSAW NEEDS

With your choice of a 13" or 15" bar, featuring a roller nose sprocket and internal fluid passages for maximum bar and chain life, the C50 HydraCutter doesn't skimp on ability, operating at 8 gpm and 2250 psi. Available with your choice of diamond-segmented chains:

- An S-series chain for cutting medium-soft to very hard aggregate with moderate to heavy steel reinforcing
- An L-series chain for cutting newer concrete, brick and concrete block without steel reinforcing

C50 -	8 GPM	HydraCutter Bars, Chains & Parts
Part #	Model	Description
1911916		13 in. C50 Bar (33 cm)
1911919		15 in. C50 Bar (38 cm)
5260501	50-S	Chain for 13 in. C50 Bar (Replaces SL25-50)
5211134	50-L	Chain for 13 in. C50 Bar (Replaces SL45-50)
5260551	55-S	Chain for 15 in. C50 Bar (Replaces SL25-55)
5211154	55-L	Chain for 15 in. C50 Bar (Replaces SL45-55)
6711964		C50 Drive Sprocket (9 Tooth)
5807195		Trantorque® Shaft Adapter
1909609		ILP™ Auxiliary Hydraulic In-Line Pump



#1911013 C50-8 GPM w/13" Bar & S or L Chain #1911015 C50-8 GPM w/15" Bar & S or L Chain



FS20 Flush Cut Saw

FS20 FLUSH CUT SAW AND BLADES

MOVE UP IN THE WORLD OR DOWN DEEP INTO A PROJECT WITH RGC'S FLUSH CUT SAW

FS20 Flush Cut Saw

All saws include Guard, Water Attachment for wet cutting, Hose whips w/ Flush-Face fittings and Trigger Lockout. (Hydraulic requirements: 8 gpm @ 2000-2500 psi.)

Part #	Description	Weight
2020305	FS20 Hand Saw, Guard and Depth Guide w/8 in. cutting depth. 1830 rpm @ 8 gpm	57 lbs.
2020201	FS20 Hand Saw, Guard, Depth Guide and Upright Handle w/8 in. cutting depth. 1830 rpm @ 8 gpm	98 lbs.
2020203	FS20 Upright Saw w/ 8 in. cutting depth. 1830 rpm @ 8 gpm	83 lbs.
2020409	FS20 Upright Handle Kit	41 lbs.

	FS20 Flush Cut Blades			
Part #	Description			
	Premium Blades			
5252001	20 in. x .125 in. – with Heavy Rebar			
5252002	20 in. x .125 in. – with Standard Rebar			
	Standard Blades			
5212211	21 in. x .125 in. – Abrasive without Rebar			
5212212	21 in. x .125 in. – Med-soft, very-Hard with Rebar			
5212213	21 in. x .145 in. – Abrasive without Rebar			
5212214	21 in. x .145 in. – Med-soft, very-Hard with Rebar			



Hydrasaws & Hydracarts



HYDRASAWS AND ACCESSORIES

WHATEVER DIRECTION YOUR WORK TAKES YOU, HYDRASAWS CAN HANDLE IT

HydraSaws & Accessories				
	All saws include Guard, Water Attachment for wet cutting, Hose whips w/ Flush-Face fittings and Trigger Lockout. (Hydraulic requirements: 5-8 gpm @ 2000-2500 psi.)			
Part #	Model	Description	Weight	
2001400	S14	14 in. circular saw w/ $5\frac{1}{4}$ in. cutting depth. 4100 rpm @ 8 gpm	28 lbs.	
2001600	S16	16 in. circular saw w/ 6 in. cutting depth. 2750 rpm @ 8 gpm	39 lbs.	
2002000	S20	20 in. circular saw w/ $7\frac{1}{2}$ in. cutting depth. Auxiliary Handle kit included. 1830 rpm @ 8 gpm	52 lbs.	
2002400	S24	24 in. circular saw w/ $9\frac{1}{2}$ in. cutting depth. Auxiliary Handle kit included. 1455 rpm @ 8 gpm	55 lbs.	
2011460		Wall Mount HydraSaw Guide 39" Kit*	34 lbs.	
2011465		Wall Mount HydraSaw Guide 84" Kit*	44 lbs.	
2011470		Wall Mount HydraSaw Guide Door Kit*	54 lbs.	



^{*}Wall Mount Guide Kits are designed for use with S14, S16, S20 & S24

HydraCarts				
Part #	Description	Weight		
2000483	HydraCart with Ballast Box for slab sawing. (Accommodates 14 in., 16 in., 20 in. and 24 in. HydraSaws)	260 lbs.		
2000489	SawCart for light duty straight linecutting. (Accommodates 14 in. and16 in. HydraSaws)	74 lbs.		





Hydrapaks With Gas Engines

HYDRAPAKS

GAS OR ELECTRIC, WE'VE GOT YOU COVERED

Whether working indoors or out, RGC HydraPaks provide the reliable, steady power your hydraulic tools need to keep your project moving on time and on budget.

HydraPaks with Gas Engines

Standard features for RGC HydraPaks with gas engines include electric start, 6 gallon hydraulic reservoir, lifting eye, low oil shutdown and a heavy-duty heat exchanger. Each unit is mounted on a portable cart with 16 in. pneumatic tires.

Part #	Model	Description	Dry Weight
2544501	HH1358	13 hp Honda with 5 or 8 gpm output @ 2250 psi max with hour meter $$	324 lbs.
2512161	HV1658	16 hp B&S Vanguard with 5 or 8 gpm output @ 2250 psi with hour meter	226 lbs.
2514408	HV1858	18 hp B&S Vanguard with 5 or 8 gpm output @ 2250 psi with electronic governor & hour meter	240 lbs.
2514404	HV1810XL	18 hp B&S Vanguard with 0 -10 gpm output and three pressure settings (1750, 2000, & 2500 psi) with electronic governor, pressure gauge, hour meter, volt meter and deluxe wide tires	336 lbs.
2542010	HH2010	20 hp Honda with 0 -10 gpm output & three pressure settings (1750, 2000 & 2500 psi) with pressure gauge, hour meter & volt meter	285 lbs.
2512234	HH2212	22 hp Honda with 0 - 12 gpm output & three pressure settings (1750, 2000, 2500 psi) with pressure gauge, hour meter & volt meter	360 lbs.
2512232	HV2312	23 hp B&S Vanguard with 0 - 12 gpm output & three pressure settings (1750, 2000, & 2500 psi) with pressure gauge, hour meter & volt meter	280 lbs.

HV1658 HydraPak
HV1810XL HydraPak
HV2312 HydraPak

HydraPaks with Dual Output				
Dual power HydraPak capable of supporting two tools at up to 12 gpm simultaneously				
Part #	Dry Weight			
2535202	HV351212	35 hp B&S Vanguard operates two tools at 0-12 gpm simultaneously; w/ electronic governor & hour meter.	410 lbs.	



HV351212 Dual Power HydraPak

^{* * *} Contact us directly for Breaker availability at 1.800.831.8665. * * *



Hydrapks With Electric Motors



	HydraPaks with Electric Motors				
	6 gallon res	powered HydraPaks are equipped with an electric motor servoir, heavy-duty heat exchanger and lifting eye. Each ounted on a portable cart with 16 in. pneumatic tires.	,		
Part #	Model	Description	Dry Weight		
2578102	HE1058	10 hp, 3ph 208-230 V, 60hz electric motor with 5 or 8 gpm output @ 2250 psi; with hour meter (Does not include motor starting or switching equipment.)	221 lbs.		
2578135	HE1058	Same as 2578102 with motor starter	232 lbs.		
2578138	HE1058	Same as 2578102 with 460V & motor starter	250 lbs.		
2578140	HE1512	15 hp, 3ph, 208-230 V, 60 hz electric motor with 0-12 gpm output and three pressure settings (1750, 2000 psi continuous duty & 2500 psi intermittent duty only) Includes motor starter, pressure gauge, hour meter, volt meter & deluxe wide tires	280 lbs.		
2578142	HE1512	Same as 2578140 with 460V	310 lbs.		



Electric HydraPak Motor Starter

Hydraulic Flow Divider				
Part #	Model	Description		
1647902	HFD	Flow Divider with Hose Whips and Flush-Face Fittings. Adjustable output of 4 - 12 gpm. Maximum input of 30 gpm and 3000psi.		



Hydraulic Hoses					
Part #	Description	Weight			
1649116	$\frac{1}{2}$ in. x 25 ft. pair Extension Hoses with Flush-Face Fittings.	21 lbs.			
1649117	$\frac{1}{2}$ in. x 50 ft. pair Extension Hoses with Flush-Face Fittings.	38 lbs.			
1649108	$^{1}\!/_{2}$ in. x 25 ft. Extension hoses with 3/4 in. Return Line, both with Flush-Face Fittings.	35 lbs.			
1601180	Pair of $\frac{1}{2}$ in. x 12 in. Hose Whips (for Drills, Impact Wrenches, Pole Saws & Hand Chain Saws).	2 lbs.			
1605621	$\frac{1}{2}$ in. x 12 in. Hose Whips (for Pole Tampers).	2 lbs.			
6316475	Biodegradable Oil – per gallon.	9 lbs.			



Hydraulic hoses



Hydraulic Pumps & Core Drills


HYDRAULIC WATER & TRASH PUMPS HYDRAULIC CORE DRILLS

Hydraulic Water & Trash Pumps				
Part #	Model	Description	Weight	
2102010	PW200	2" Submersible Water Pump - Max. 250 gpm capacity & 145' lift height. (Requires 5-8 gpm @ 1200-2000 psi.)	12 lbs.	
2127525	PW250	2½" Submersible Water Pump - Max. 275 gpm capacity & 145' lift height. (Requires 4-8 gpm @ 2000 psi.)	12 lbs.	
2150030	PW300	3" Submersible Water Pump - Max. 500 gpm capacity & 120' lift height. (Requires 7-11 gpm @ 2000 psi.)	21 lbs.	
2103008	PT300	3" Submersible Trash Pump -Max. 475 gpm capacity & 100' lift height. (Requires 6-10 gpm @ 1500-2000 psi.)	36 lbs.	
2187540	PT400	4" Submersible Trash Pump - Max. 875 gpm capacity & 45' lift height. (Requires 7-9 gpm @ 2000 psi.)	59 lbs.	
2100221		2" Hose x 25' Long w/ Cam-Lock Fittings		
2100311		3" Hose x 25' Long w/ Cam-Lock Fittings		



Water Pump

Hydraulic Core Drills				
Part #	Model	Description	Weigh t	
1715007	CD616	Hydraulic Core Drill for 6 in. to 16 in. drill bits(1¼ in. UNC thread). Has variable speed control. Hose whips and M2 Drill Stand with 42 in. mast and spacers with bolts included. Max. 330 rpm @ 8 gpm. (Requires 8 - 15 gpm @ 2000-2500 psi)	158 lbs.	
1715008	CD1824*	Hydraulic Core Drill for 18 in. to 24 in. drill bits ($1\frac{1}{4}$ in. UNC thread). Has variable speed control. Hose whips and M2 Drill Stand with 42 in. mast and spacers with bolts included. Max. 200 rpm @ 8 gpm. (Requires 8 – 15 gpm @ 2000 - 2500 psi)	163 lbs.	



10 |


Platform Hoists




Classic Drive Hoist Specifications

Classic Drive Hoist Specifications					
400 200					
Load Capacity	400 lbs.	200 lbs.			
Lift Speed	110 fpm	220 fpm			
Platform size	24 in. x 24 in.	17 in. x 18 in.			
Track (3-3/4 in. side rail)	24 in. wide	17 in. wide			

Track Length	Option A	Option B*
12 ft	8' base + 4' track	n/a
16 ft	16' base	8' base + 8' track
28 ft	16' base + 8' track + 4' track	8' base + (2) 8' tracks + 4' track
44 ft	16' base + 16', 8' & 4' track	8' base, (4)-8' tracks + 4' track





Classic 200 lb. Platform Hoists

Part #	Part Name	Track Size	Engine/ Motor	Weight
0431216	Classic G-16 ft.	16 ft.	4 hp B & S gas	221 lbs.
0450923	Classic HG-16 ft.	16 ft.	4 hp Honda gas	228 lbs.
0431116	Classic E-16 ft.	16 ft.	11/2 hp electric	247 lbs.
0431228	Classic G-28 ft.	28 ft.	4 hp B & S gas	251 lbs.
0450924	Classic HG-28 ft.	28 ft.	4 hp Honda gas	258 lbs.
0431128	Classic E-28 ft.	28 ft.	11/2 hp electric	277 lbs.
0431244	Classic G-44 ft.	44 ft.	4 hp B & S gas	339 lbs.
0450925	Classic HG-44 ft.	44 ft.	4 hp Honda gas	346 lbs.
0431144	Classic E-44 ft.	44 ft.	1½ hp electric	365 lbs.

Classic 400 lb. Platform Hoists

Part #	Part Name	Track Size	Engine/ Motor	Weight
0431416	Classic G-16 ft.	16 ft.	4 hp B & S gas	256 lbs.
0450944	Classic HG-16 ft.	16 ft.	4 hp Honda gas	263 lbs.
0431316	Classic E-16 ft.	16 ft.	1½ hp electric	282 lbs.
0431428	Classic G-28 ft.	28 ft.	4 hp B & S gas	289 lbs.
0450945	Classic HG-28 ft.	28 ft.	4 hp Honda gas	296 lbs.
0431328	Classic E-28 ft.	28 ft.	1½ hp electric	315 lbs.
0431444	Classic G-44 ft.	44 ft.	4 hp B & S gas	380 lbs.
0450946	Classic HG-44 ft.	44 ft.	4 hp Honda gas	387 lbs.
0431344	Classic E-44 ft.	44 ft.	11/2 hp electric	406 lbs.

^{***}Classic 12 foot Hoist Kits available upon request. ***

Pivoting Platform Hoist—PPH 400 lb. Capacity

		Track		
Part #	Name	Size	Engine/Motor	Weight
0421443	PPH Classic G-44 ft.	44 ft.	4 hp B & S gas	430 lbs.
0421445	PPH Classic HG-44 ft.	44 ft.	4 hp Honda gas	436 lbs.
0421441	PPH Classic E-44 ft.	44 ft.	11/2 hp electric	457 lbs.

Power Drives

Part #	Part Name	Weight
0413041	Classic Drive w/ 4 hp. Briggs & Sratton Gas Engine	128 lbs.
0413042	Classic Drive w/ 4 hp. Honda Gas Engine	135 lbs.
0432504	Classic Drive w/ 1½ hp. Electric Motor	154 lbs.



^{* * *} To see our full line of Hoisting Equipment, visit our website at www.rgchoisting.com or contact us at 1.800.831.5438 to request a brochure. * * *

SEE OUR FULL LINE OF HOISTING EQUIPMENT AT WWW.RGCHOISTING.COM OR REQUEST A FULL LINE CATALOG TODAY AT 1-800-831-LIFT (5438)





PROUDLY BUILT TO LAST IN THE USA FOR 75 YEARS 25



1849 HARLEM ROAD | BUFFALO, NY 14212 1-800-831-TOOL (8665) | 716-895-1547 (FAX) WWW.RGCTOOLS.COM | SALES@RGCTOOLS.COM